

## No. 0314-CQL-T


1	Unique ID Code	CQL-C
2	Type	Clayfix Crushed Quicklime – CL 90 (R5,P <sub>SV</sub> )
3	Intended Use	Preparation of binder for mortar for masonry, rendering and plastering and production of other construction products, and for civil engineering applications
4	Manufacturer	Clogrennane Lime Ltd Toonagh Lime Works Ennis, Co. Clare Ireland Tel: 00353 5991 31811 Fax: 00353 5991 31607 Email: office@clogrennane.ie
5	System	2*

6	Notified Body	NSAI
7	ID No.	0050
8	Performed	Initial inspection of the manufacturing plant and of factory production control and continuous surveillance, assessment and evaluation of factory production control
9	Issued	21 <sup>st</sup> July 2005 (under CPD)

Essential Characteristics	Performance	Harmonised Technical Specification
CaO + MgO	> 90 %	EN459-1 : 2010
CO <sub>2</sub>	< 4%	
SO <sub>3</sub>	< 2%	
Available Lime	> 85%	
Reactivity	R5	
Particle Size Distribution	P <sub>SV</sub>	
Soundness	Pass	
Durability	The choice of calcium lime, particularly as regards types for different applications and exposure conditions shall follow the appropriate European or national application standards and/or regulations valid in the place of use	

This declaration of performance is issued under the sole responsibility of the manufacturer identified in Point 4 above

Signed for and on behalf of the manufacturer:



Joe Connolly

Technical Manager  
Clogrennane Lime Ltd

1<sup>st</sup> July 2014